



# PHILLIP JEFFRIES LTD. HANGING INSTRUCTIONS

## WOVEN LEATHER WALLCOVERINGS

**STOP: DO NOT CUT OR INSTALL UNTIL YOU HAVE READ THESE INSTRUCTIONS!**

Thank you for choosing this high quality vinyl wallcovering. For the best results, we believe that a professional wallcovering installer should hang these wallcoverings.

### **DESCRIPTION:**

Old school luxury meets new school innovation with the exquisite **WOVEN LEATHER** collection of vinyl wallcovering. Developed to bring the look and feel of handcrafted leather to the walls, a pattern of approximately 2" squares is embossed for a luxurious woven effect. Made from 54" Type II 20 oz. vinyl with an Osnaburg backing, **WOVEN LEATHER** is highly durable, washable and suitable for commercial as well as residential interiors.

### **PREPARATION:**

Before you cut and hang, please be sure you have:

1. The correct wallcovering and the correct amount of wallcovering to finish the job.
2. Inspect the wallcovering carefully to ensure it is free of defects:

If no defect is evident before installation, the material should be inspected after three (3) strips are installed. If any defect is evident at this time (or at any point in the installation) no additional material should be hung until Phillip Jeffries Ltd. is notified. **NO CLAIMS WILL BE ALLOWED FOR MORE THAN (3) STRIPS ON THE WALL.** All claims must be made within 60 days of the invoice date. No labor claims will be allowed at any time.

**BUILDING & MATERIAL CONDITIONS:** The building must be weather-tight with HVAC settings (including pressure, temperature and relative humidity) the same as those of an occupied building for three days prior to, throughout installation and three days after installation. The walls must be structurally sound including elimination of sources of moisture accumulation into the wall or wall cavity. The wallcovering must be in a clean and dry condition and must be stored at normal occupied building temperature and humidity for at least three days prior to installation. All adhesives and primers must be new, good quality, commercial grade materials, which have not been contaminated.

**IF YOU HAVE ANY QUESTIONS, PLEASE STOP AND CONTACT  
PHILLIP JEFFRIES LTD. BEFORE PROCEEDING.**

### **WALL PREPARATION:**

1. The walls to be covered must be properly prepared to ensure that the wallpaper will adhere to the wall surface. Even the strongest adhesive can only work when the wall surface is clean and properly prepared.
2. Please be sure to cover old latex paint and new sheetrock or very absorbent walls with a good quality primer that is **SPECIFICALLY MADE FOR WALLCOVERING**. The exact primer must be determined by the installer. However when covering flaky or water based paint, a heavy duty wallcovering primer may provide the best results.
3. Allow the primer to dry thoroughly before hanging.

311 Route 46 Fairfield, NJ 07004

Phone: 800-576-5455 Fax: 888-759-8878

Email: customerservice@phillipjeffries.com



# PHILLIP JEFFRIES LTD.

## HANGING INSTRUCTIONS

### WOVEN LEATHER WALLCOVERINGS

**STOP: DO NOT CUT OR INSTALL UNTIL YOU HAVE READ THESE INSTRUCTIONS!**

#### INSTALLATION

##### ADHESIVE

1. We recommend a clear, non-staining, pre-mixed vinyl adhesive.
2. Apply the paste to the back of the paper using a pasting machine, or for hand application a short napped paint roller.

##### TRIMMING

1. We strongly recommend creating a precision trimmed edge by trimming the wallcovering on your work table or by making a double cut on the wall.
2. We strongly recommend making the vertical trim line at the edge of a square for a clean match, not in the middle of the square.
3. Trim edges with a VERY sharp razor blade. Change your blades often.
4. Squares are approx. 2" x 2" (5.08 cm x 5.08 cm). Woven leather is meant to match randomly.
5. Side Note: Product has a full 27" horizontal repeat. Manufacturer recommends matching along edge of 2" squares.

##### TIPS

1. All strips should be hung in sequence, as they come off the roll.
2. Gently smooth the wallcovering using a plastic smoother. Do not use a seam roller.
3. Remove excess adhesive and dirt from wallcovering surface and seams immediately, using a sponge or damp cloth frequently rinsed in clean, warm water.
4. Vinyl wallcoverings should be washed regularly to prevent dirt and grime from accumulating. Depending on traffic (light, medium, heavy), vinyl should be washed two or three times a year.
5. Ordinary dirt can be removed with mild soap and warm water. Dry wallcovering with a soft, lint-free cloth or towel. Do not use hard bristle brush or metal sponge such as Brillo on wallcovering. For more difficult stains that are only surface deep, the use of a stronger detergent is recommended. WE RECOMMEND ALL CLEANERS BE TESTED IN AN INCONSPICUOUS AREA TO INSURE COMPATIBILITY WITH THE WALLCOVERING.